

Section B26 Miscellaneous Components


B26.1 Highfield Levers

The most common application for highfield levers is on an inner forestay, enabling the inner forestay to be easily connected or disconnected. This is useful on a cutter rig, enabling the inner forestay to be released and stowed against the mast when gybing the spinnaker pole, then reconnected and tensioned. Similarly on a boat on which a staysail set on an inner forestay is used only temporarily, such as when heavily reefed, a highfield lever on the inner forestay simplifies the setup process.

The double action highfield lever is suitable for a wire range of 5.5 to 9.5mm. The lever is self-locking, however it is recommended that it also be fixed back with rings, lashing or even a leather or tubular hood (not supplied). A single action highfield lever is also available.

Note: A rigging screw is not supplied as part of the highfield lever.

PART NO.	ACTION	PIN SIZES		WIRE SIZES mm
		(mm)	(in)	
026.026	Double	12.7	½	6.5
				7
				8
026.027	Double	15.9	5/8	9.5



B26.2 Pad Eyes

The Angled Pad Eye is designed to fit on the back of the mast below the gooseneck, to carry a snatch block for the purpose of turning a reefing line, exiting from the inner end of the boom, back up to a mast-mounted winch.

DESCRIPTION	PART NO.
Angled pad eye - heavy duty	026.201

